



## Pineline Comp-clean LT

Product no.	215								
Description	Highly alkaline detergent concentrate for wheel-washing machines in vehicle repair workshops. Also suitable for chamber washers in the metal and workshop industry.								
Special features	Low-foaming also at low temperatures. Removes road salt, soot, brake dust, cooling lubricants and protective agents.								
Instructions for use	<u>Wheel-washers:</u> Dilution 0.5 – 1 %. Temperature of washwater: 5 – 80 °C. <u>Chamber washing machines:</u> Make sure that there is no detergent or dirt residue in the washing machine. Add detergent concentrate to 70 – 80 °C wash water, concentration 1 – 3 %. Add the product to the washing machine on a regular basis to maintain washing power and to prevent corrosion.								
Note!	Read the instructions for safe use on the label or in the Safety Data Sheet. Store sealed at +5...+30 °C.								
Working environment	Ensure adequate ventilation. The product is easily biodegradable and meets Ecolabel requirements.								
Technical data	<table><tr><td>Form and colour</td><td>clear liquid</td></tr><tr><td>pH-value(20 °C)</td><td>13.3</td></tr><tr><td>pH-value(1 wt-%, 20 °C)</td><td>11.2</td></tr><tr><td>Relative density</td><td>1.04</td></tr></table>	Form and colour	clear liquid	pH-value(20 °C)	13.3	pH-value(1 wt-%, 20 °C)	11.2	Relative density	1.04
Form and colour	clear liquid								
pH-value(20 °C)	13.3								
pH-value(1 wt-%, 20 °C)	11.2								
Relative density	1.04								
Contents	Potassium hydroxide < 2 %.								
Package	25 L, 200 L.								
Other information	Transportation class: UN 3266. Made in Finland.								

14.3.2018