

## Pineline Pressure Wash HD

|                      |  |                                      |
|----------------------|--|--------------------------------------|
| Product no.          | 760  |                                      |
| Description          | Highly alkaline detergent concentrate for cleaning transport, excavation, lifting, garden and process equipment. Also suitable for maintenance-related cleaning, industrial process equipment cleaning, and surface cleaning prior to treatment. |                                      |
| Special features     | Removes resin, grease, waxes, insect residues, grass stains, waterborne paints, etc. Effective for cleaning truck tarpaulin covers. Also suitable for dispensing via high pressure and steam cleaners.   |                                      |
| Instructions for use | Dilution 1 – 30 %. Temperature of wash water: 5 – 80 °C.<br>Soaking time 1 – 5 min. Rinse thoroughly with water.   |                                      |
| Note!                | Do not spread the product onto light-metal, galvanised or other sensitive surfaces. Read the instructions for safe use on the label or in the Safety Data Sheet. Store sealed at +5...+30 °C.  |                                      |
| Working environment  | Ensure adequate ventilation. The product is easily biodegradable and meets Ecolabel requirements.  |                                      |
| Technical data       | Form and colour<br>pH-value(20 °C)<br>pH-value(1 wt-%, 20 °C)<br>Relative density  | clear liquid<br>13.8<br>11.9<br>1.06 |
| Contents             | Non-ionic surfactants<br>Sodium hydroxide  | 15 – 30 %.<br>< 5 %.                 |
| Package              | 25 L, 200 L, 1000 L.   |                                      |
| Other information    | The product has the right to use the Nordic Swan Ecolabel (licence no. 4065-0006). Transportation class: UN 3266. Made in Finland.   |                                      |

12.3.2018